



NAPOLI TRAD. 110 WOOD

SERIES: PAVESI TRADITIONAL BRICK OVENS



Standard Napoli
Traditional 110
Wood/Gas

JOB NAME: _____

REFERENCE INVOICE #: _____

CUSTOM FACADE: ☐ YES ☐ NO

CUSTOM FACADE DOCUMENT #: _____

• Napoli Traditional 110 is constructed in a place by a certified Fiero Forni Technician.

REFRACTORY MONOBLOCK FLOOR

The Napoli Traditional features the world's only refractory commercial brick oven floor in one solid block.

TRADITION & TECHNOLOGY

The Napoli Traditional is designed to preserve traditional Italian hearth oven dynamics with maximum consistency for high output.

VERSATILE & RELIABLE




The Napoli Traditional design exceeds at holding a wide variety of temperatures to achieve almost any pizza size and style.



Approved by
the Association
of Neapolitan
Pizzaiuoli of
America

FEATURES

The Napoli Traditional 110 is a hand-built Italian hearth-style brick oven manufactured in the USA with an imported Pavese Italian hearth. The solid, single piece refractory floor diameter is 43 1/3", with a front-facing steel arch opening which allows access to the hearth at 19" wide by 9.5" tall. Wood fuel is combusted directly within the oven hearth which maximizes energy efficiency and power. The internal refractory dome and single piece floor are sealed with a refractory cement and over-insulated with high quality asbestos-free ceramic blankets to ensure maximum heat retention. The oven structure is formed by a formed dome finished with Venetian mosaic 1"x1" tile and sits on top of four square black steel legs. The oven may optionally be supplied with a single-flame powered gas burner for use as a primary oven heat source. The self-modulating gas burner monitors the oven floor temperature to adjust the BTU input for maximum efficiency and steady performance. Custom facade options can be found online at www.fierogroup.com.

BAKING SURFACE	OVEN OPENING	EXTERNAL WIDTH	EXTERNAL DEPTH
			

OVEN PRODUCTION

12" PIZZA CAPACITY: 4 PIZZAS


RECOMMENDED BAKING TIME: 90 - 240 SECONDS (DEPENDENT ON PIZZA STYLE)

RECOMMENDED OVEN FLOOR

TEMPERATURE RANGE: 600°F - 900°F
(DEPENDENT ON PIZZA STYLE)

DAILY PREHEAT TIME: 30 MINUTES

CUSTOM FACADE OPTIONS



TILE



STUCCO

(Please circle one. Depending on your preference, a custom facade worksheet will be sent to you)

FIERO GROUP
601 N Main St, Brewster, NY 10509
Email: info@fierogroup.com
www.fierogroup.com

844-OVEN-INC (844-683-6462)
Toll-free in USA
(Hablamos Español,
Falamos Português)

Listed to: UL 2162-ULC/ORD C2162,
ANSI Z83.11-CSA 1.8, & NSF-4 for
Commercial Wood Fired and
Gas Fired Cooking Equipment



DOC#: NAPTR-0320

REVISED SPRING 2022. As products continue to improve, spec sheets may change without notice. Please call Fiero Group for the latest specification sheet and for further details.

MADE IN ITALY AND USA




NAPOLI TRADITIONAL 110 WOOD

SERIES: PAVESI TRADITIONAL BRICK OVENS

DETAILED SPECS

PLAN VIEW




WEIGHT:
2,370 LB


We make every effort to provide accurate information regarding manufacturer's reported dimension information. Please note that due to the artisan nature of the manufacturing process, from time to time, product sizing and ship weight may vary slightly.

NOTE:
DIM.s WITHOUT TILES
AND GROUT

FRONT ELEVATION



RIGHT ELEVATION



KEY



Flue Collar
Exhaust Connection

All measurements listed in inches and millimeters

CLEARANCES

Minimum clearance of the oven (built-in or standalone) to combustible materials are as follows:

Top: 14" (356 mm)

Back & Sides: 1" (25 mm)


- Non-combustible flooring must extend out at least 36" (914 mm) from oven opening and at least 30" (762 mm) to each side of the opening.
- Do not fill required air space with insulation or other materials.

VENTILATION REQUIREMENTS

Direct connection as a natural draft, grease-rated chimney system per NFPA 96 and UL 2162 is recommended. If the duct run exceeds 20 feet or incorporates a 90° elbow, a UL 705 & UL 762 listed rooftop exhaust fan shall be installed to ensure adequate pressure within the duct. A Listed Type 1 exhaust hood, or one constructed in accordance with

all relevant local and national codes (NFPA 96), may also be installed above the oven in instances where a natural/power draft chimney system is otherwise impossible. See "Ventilation Document - Pavesi" for details.

Operational airflow: 150-200 CFM
Static Pressure at Flue Collar: 0.05 in H₂O



FLUE COLLAR
CONNECTION
DIAMETER
(EXTERNAL)

ELECTRICAL REQUIREMENTS

Wood-fired

- No electrical connection

WARRANTY INFORMATION

10 year limited warranty on internal refractory parts, 1 year limited warranty on other components. See warranty document for details.

FIERO GROUP
601 N Main St, Brewster, NY 10509
Email: info@fierogroup.com
www.fierogroup.com

844-OVEN-INC (844-683-6462)
Toll-free in USA
(Hablamos Español,
Falamos Português)

Listed to: UL 2162-ULC/ORD C2162,
ANSI Z83.11-CSA 1.8, & NSF-4 for
Commercial Wood Fired and
Gas Fired Cooking Equipment



DOC#: NAPTRAD-0322

REVISED SPRING 2022. As products continue to improve, spec sheets may change without notice. Please call Fiero Group for the latest specification sheet and for further details.

MADE IN ITALY AND USA