



PCB-24



Intertek
 4004503
 Conforms to ANSI/NSF STD 2

To view underbar installation instructions, please visit: https://www.glastender.com/PDF/F-750-165_Underbar_Installation_Instructions.pdf
 To view cleaning and care instructions, please visit: https://www.glastender.com/PDF/F-423-011_ss_clean_care.pdf

Side Splash Accessories

***NOTE: Verify cash drawer width before ordering side splash accessories.**



With LSP accessory



With RSP accessory



With LSP and RSP accessories

Project: _____	AIA# _____
Item #: _____ Qty: _____	SIS# _____
Model #: _____	

POS Cabinets

PCB-18, PCB-24

Standard Features

- All stainless steel construction with adjustable bullet feet
- One-piece, seamless top and backsplash
- Louvered door features integral handle
- Door lock standard
- Special 26" high work surface height to accommodate cash drawer and POS monitor
- Grommated cord access hole in work surface
- Large access hole in back wall of unit
- Smooth interior walls for easy cleaning and a finished appearance
- *Models available with left and/or right side splashes. Specify accessory number LSP (left side) and/or RSP (right side)

Specifications

Legs

- 1-5/8" diameter, 16 gauge stainless steel
- Stainless steel bullet feet

Materials

- 20 gauge stainless steel parts include: all components unless otherwise noted
- 18 gauge stainless steel parts include: leg pads

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780
 989.752.4275 • 800.748.0423 • Fax 989.752.4444
www.glastender.com

Approval/Notes:

Specifications subject to change without notice. For current specifications please visit our website.

POS Cabinets

Dimensional Information

Model Number	X - OD No Side Splashes	Y - ID w/ LSP and RSP accessories*
PCB-18	18"	17-7/8"
PCB-24	24"	23-7/8"

***NOTE: Verify cash drawer width before ordering side splash accessories.**

