JOB	ITEM#	QTY/MODEL#

CVAP® HOLDING CABINETS HOV3

HOV3 SERIES

HOV3-05UV | HOV3-10UV | HOV3-14UV

CVap Holding Cabinet: Includes Membrane Control, and Convection Holding.

SHORT FORM SPECS

Shall be Winston CVap Holding Cabinet, model _____. Unit to utilize a membrane control with processor to control calibration-free thermistors to adjust evaporator and air temperatures in 1°F increments.

CONFIGURATIONS

Half-Sized: Easily mobile versions, allowing operator to see over cabinet when transporting. Most half-sized units are also stackable for increased versatility.

Full-Sized: Provides maximum capacity for high volume operators.

CVap® ADVANTAGE
The original humidified holding cabinet is still the best. CVap technology uses dry and vapor heat, in tandem, to control food temperature, and maintain it as moist or crisp as you want. Learn more at winstonfoodservice.com.

Model Shown: HOV3-14UV
with solid doors



MODEL TYPE	MC	WC	FP	HD	CM	AP
HOV3	YES	NO	NO	NO	ON	NO

MC - Membrane Control
WC - Wireless Connectivity
FP - Food Probe Ready
HD - HACCP Temp Download
CM - Convection Mode
AP - Audio

WINSTON FOODSERVICE
2345 Carton Drive | Louisville, KY 40299 USA | winstonfoodservice.com | 800.234.5286 | +1.502.495.5400

Specifications subject to change without notice.

JOB | ITEM# | QTY/MODEL#

CVAP® HOLDING CABINETS HOV3

Cabinet Specifications

HOV3-05UV | HOV3-10UV | HOV3-14UV

MODEL NUMBER DESCRIPTIONS

EQUIPMENT TYPES
HO = HOLDING
CH = COOK/HOLD
RT = RETHERM
UB = UNIVERSAL BIN



PAN CONFIGURATIONS
HP = HALF PAN
SP = SHEET PAN
UV = UNIVERSAL

	CAPACITY			EXTERIOR DIMENSIONS **				ELECTRICAL						
MODEL #	SHEET PAN (18" x 26")	HALF SHEET PAN (18" x 13")	HOTEL PAN (12" x 20" x 2.5")	STANDARD CASTER SIZE	HEIGHT IN.(MM)	DEPTH IN.(MM)	WIDTH IN.(MM)	VOLTS	PHASE	WATTS	AMPS	NEMA***	INT'L	SHIP WEIGHT LBS(KG)
HOV3-05UV	5	10	10	3"	39.41(1001)	34.23(869)	27.70(704)	120	1	1800	15	5-15P	Call Factory	250(113)
HOV3-10UV	10	20	20	5"	61.66(1566)	34.23(869)	27.70(704)	120	1	1800	15	5-15P	Call Factory	303(138)
HOV3-14UV	14	28	28	5"	75.66(1922)	34.23(869)	27.70(704)	120	1	2292	19.1	5-20P	Call Factory	420(190)

*Capacity - Determined by 3.5" (89mm) adjustable spacing, with a load limit of 65lb (29.25kg) per rack. | **Exterior Dimensions - Cabinet height is calculated with standard caster size. If 3" caster is standard, subtract 2.48" (63mm) for 1.5" wheels, add 2.31"(59mm) for 5" casters, subtract .25"(6mm) for 4" legs, and add 1.63"(41mm) for 6" legs. If 5" caster is standard, subtract 2.31"(59mm) for 3" casters, and subtract .69"(18mm) for 6" legs. | ***NEMA - Supplied with 84" (2134mm) (minimum) power cord and plug. The input average of current did not exceed the allowable amperage for the circuit listed.

CONTROL: Membrane control with vapor and air temperatures to be adjusted in 1°F increments. Processor controlled calibration-free thermistors, accurate within +/- 2°F and accommodates software updates via USB.
MATERIALS: To be commercial and institutional grade stainless steel interior and exterior.
DOORS: Insulated field-reversible door with magnetic handles. Full-sized units to include two dutch doors. Doors may be specified with windows, pass-through, or a combination of both.
WATER FILL: Operated manually with low water detection. Auto-fill optional. Low mineral potable water recommended, otherwise use deionizer/demineralizer to minimize corrosion damage.
INSTALLATION REQUIREMENTS: Units to be installed with 2" (51mm) clearance on sides and may not be installed within proximity to anything emitting heat that would allow the exterior of the Winston cabinet to exceed surface temperatures of >200°F. Refer to owner's manual for specific installation requirements.
INDUSTRY COMPLIANT: Equipment complies with domestic and most international requirements; such as UL, C-UL, UL Sanitation, CE, MEA, EPA202, and others.
WARRANTY: Limited one-year warranty (excludes gaskets, lamps/lights, hoses, power cord, glass panels, and evaporator). Warranty disclaimer for improper cleaning, installation, and/or maintenance. Ask for complete warranty disclosure.

SPECIFY THE FOLLOWING WHEN ORDERING:

Standard (No additional cost):
1. Hinge Preference: Left or right hinge
2. Casters: See table above for standard caster size, addtional options include 3" caster, 5" caster, and 6" legs.

Optional (Additional cost):
- Pass Through
- Pass Through-Glass
- Bumper Guard Base
- Extended Warranty
- Glass Door
- Cord Wrap
- Reinforced Top**
- Transport Package
- Auto Water Fill
- Locking Door***

** Available for 05UV only
*** Quantity of 1 for reach in. Quantity of 2 for pass-through. Customer to provide padlock(s) (per door).

Accessories & Supplies (Additional cost):

PS2206-4	Wire rack-chrome (4-pack)
PS2206-5	Wire rack-chrome (5-pack)
PS2938-4	Wire rack-stainless steel (4-pack)
PS2980-2	Wire rail (2-pack)
PS2696	Mobile water removal system
PS3171	Leg and shelf kit for 05UV
PS3174	Stacking kit for 05UV
PS3167	Drain kit for stacked pair
AC1006	8.125" top extension (14UV model only)
AC1008	Cover, Rear Fan

FOR WINSTON SERVICE PARTS, ACCESSORIES, AND SUPPLIES ONLINE!
foodservice.winstonind.com/parts-supplies

WINSTON FOODSERVICE
2345 Carton Drive | Louisville, KY 40299 USA | winstonfoodservice.com | 800.234.5286 | +1.502.495.5400

Specifications subject to change without notice.

Copyright © 2024
doc20200116wlp1rev18 | wp 06.10.24