



Shown With Optional Speed Rail

FEATURES:

10.178" or 14.178" deep ice bin.

Two removable injection molded 3-pack plastic bottle racks.

1 3/4" return w/ soda gun knock-out.

7" Backsplash

Stainless steel top, apron and sides.

Optional 10-circuit cold plate sealed into bottom of ice bin.

Adjustable side cross-bracing

PRI-24 Series has rear deck for extra storage.

Units with Cold Plates include a soda line chase at top of splash on right & left ends (For units without Cold Plates, add **Model # SU-30**).

Bottle Racks Must Be Removed For NSF Compliance
And For Use With Optional Cover.



Ice Bins (S) 20" and 25" Wide Units

ltem #:	Qty #:
Model #: _	
Project #:	

MECHANICAL:

1" IPS drain - non cold plate bin 1/2" IPS drain - cold plate bin

MATERIAL:

20 gauge, 300 stainless steel.

Legs: 1 5/8" O.D. 18 gauge, 300 stainless steel legs with

1" adjustable stainless steel bullet feet.

Cold Plate: Cast aluminum with 10 circuits (8 syrup and 2 water lines)

with 5/16" diameter stainless steel bump and swedge ends.

Ice Bin Insulation: Foam Insulation.

OPTIONAL:

PRA-SSC-12 - Sliding cover for 12" ice bin

PRA-SSC-18 - Sliding cover for 18" ice bin

PRA-SSC-24 - Sliding cover for 24" ice bin

PRA-SSC-30 - Sliding cover for 30" ice bin

PRA-SSC-36 - Sliding cover for 36" ice bin

PRA-SSC-42 - Sliding cover for 42" ice bin

PRA-SSC-48 - Sliding cover for 48" ice bin



Optional Sliding Stainless Steel Cover Shown

For More Accessories & Modifications, Visit Us At www.advancetabco.com.

20" WIDE Model #	Approx. Weight	Approx. Cu. Ft.	25" WIDE Model #	Approx. Weight	Approx. Cu. Ft.	Overall Length (A)	Distance To Drain (B)	Inside Bin Width (C)	Ice Bin Depth	Ice Bin Capacity
PRI-19-12	55 lbs.	9	PRI-24-12	60 lbs.	11	12"	6"	9 5/8"	11" DEEP	32 lbs.
PRI-19-18	60 lbs.	9	PRI-24-18	65 lbs.	11	18"	9"	15 5/8"		51 lbs.
PRI-19-24	65 lbs.	9	PRI-24-24	70 lbs.	11	24"	12"	21 5/8"		70 lbs.
PRI-19-30	70 lbs.	14	PRI-24-30	75 lbs.	15	30"	15"	27 5/8"		89 lbs.
PRI-19-36	75 lbs.	14	PRI-24-36	80 lbs.	15	36"	18"	33 5/8"		108 lbs.
PRI-19-42	80 lbs.	19	PRI-24-42	85 lbs.	20	42"	21"	39 5/8"		127 lbs.
PRI-19-48	85 lbs.	19	PRI-24-48	90 lbs.	20	48"	24"	45 5/8"		146 lbs.
PRI-19-24-XD	80 lbs.	17	PRI-24-24-XD	85 lbs.	20	24"	12"	21 5/8"	15" DEEP	80 lbs.
PRI-19-30-XD	85 lbs.	23	PRI-24-30-XD	90 lbs.	27	30"	15"	27 5/8"		121 lbs.
PRI-19-36-XD	90 lbs.	23	PRI-24-36-XD	95 lbs.	37	36"	18"	33 5/8"		147 lbs.

With 10-Circuit Cold Plate

PRI-19-30-10	140 lbs.	21	PRI-24-30-10	145 lbs.	24	30"	15"	27 5/8"		89 lbs.
PRI-19-36-10	145 lbs.	21	PRI-24-36-10	150 lbs.	24	36"	18"	33 5/8"		108 lbs.
PRI-19-42-10	150 lbs.	26	PRI-24-42-10	155 lbs.	31	42"	21"	39 5/8"		127 lbs.
PRI-19-48-10	155 lbs.	26	PRI-24-48-10	160 lbs.	31	48"	24"	45 5/8"		146 lbs.
PRI-19-24-10-XD	160 lbs.	17	PRI-24-24-10-XD	165 lbs.	20	24"	12"	21 5/8"	15"	80 lbs.
PRI-19-30-10-XD	165 lbs.	23	PRI-24-30-10-XD	170 lbs.	27	30"	15"	27 5/8"	DEEP	121 lbs.
PRI-19-36-10-XD	170 lbs.	23	PRI-24-36-10-XD	175 lbs.	27	36"	18"	33 5/8"	DEEP	147 lbs.



DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL



