

Project: _____ Location: _____ Item #: _____ Quantity: _____

Standard Features

- Kettle System—Seamless deep-drawn 316 kettle liner with an integrally formed radius lip
- 304 stainless kettle jacket
- Kettle protection system—thermostat temperature control, 150°F - 285°F, pressure relief valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, Field replaceable heating elements
- Full body insulation between kettle jacket and outer casing
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded control console
- 304 stainless, reinforced base plate

Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet*
- Faucet bracket (ALFBT)
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALAC-WS)
- Mixer/agitator, single speed
- Correctional Package*

* Call AccuTemp for additional information

Electrical Options

208V, 240V, 380V, 415V, 440V, 480V

Short Spec

AccuTemp Edge Series countertop kettle, model ALTEH-XX (5 or 10 gallon capacity), seamless deep-drawn 316 kettle liner with integrally formed radius lip and 304 stainless kettle jacket. Full body insulation between the kettle jacket and outer casing. 2/3 jacketed with pressure relief valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light and field replaceable heating elements. Seam welded control console with thermostat temperature control, 150°F to 285°F (65°C to 140°C). Optional stand available for floor mounting.

Other Approvals



Accessories

- Care Kit (ALKCK-L)
- Lift-off cover (ALLCT-M)
- Table for one or two ALTEH kettles (ALR-343A-1, ALR-343A-2)
- Anti-splash screen for sliding drawer (ALASMS)
- Single basket insert (ALSBI-M)
- Nylon bag insert with spreader ring (ALNBI)
- Tilt locking device (ALTEH-LD)

* Call AccuTemp for additional information



Model ALTEH-5

MODEL ALTEH ELECTRICAL SPECIFICATIONS (Amperes per Leg)													
GAL	KW	208 Volt		240 Volt		380 Volt		415 Volt		440 Volt		480 Volt	
		1Ø	3Ø										
5	6	21.7	12.5	25.0	14.4	15.8	9.1	14.5	8.3	11.5	6.6	12.5	7.2
10	12	43.3	25.0	50.0	28.9	31.6	18.2	28.9	16.7	22.9	13.2	25.0	14.4

MODEL ALTEH DIMENSIONS									
GAL	A	B	C	D	F	G	J	L	W
5	14.0	9.9	27.2	11.0	26.5	4.8	32.2	23.5	11.6
10	16.0	14.0	27.2	11.0	27.0	4.8	32.2	23.5	12.6

