



## LOW HEIGHT REMOTE BACK BAR REFRIGERATOR



BBRLP48 shown



BBRLP72 shown

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS
BBRLP48
BBRLP72
BBRLP96

### KEY PRODUCT FEATURES AND BENEFITS

- Remote back bar refrigerators allow customers to mount the compressor in an alternate location, ideal for remote servicing and noise isolation
- All stainless steel interior with stainless steel or black top for long life durability and easy to clean hygienic storage
- 2" Foamed-in-place insulation provides energy savings using Ecomate™, a blowing agent that has zero-ozone depletion and zero global warming potential
- NSF/ANSI Standard 7 Listed for open food, beverage, and garnish storage
- Anti-sweat heaters in cabinet face prevents condensation from forming on door, extending door gasket life and protecting flooring below from damage or slip hazards
- Multiple door styles available in any compartment
  - Choose between Glass, Stainless-Steel, Black Vinyl, or Customer Provided Overlay
  - Drawers not available on remote models

### Additional Features:

- Choose between all stainless exterior or all black option featuring Cerakote finished black handles and door locks.
- Integrated door locks standard on all units
- Optional condensing units available
- Choose between 6000K white LED lighting or cool blue display lighting
- Choose between flat shelving and wine racks for each compartment
- Choose between Full Length, 6" Chrome, or pull tab style handles
- 1 Year Parts and Labor Warranty

### OPTIONS

MODEL NOS.	DESCRIPTION
BBRLP48	2-door model
BBRLP72	3-door model
BBRLP96	4-door model



# PERLICK®



MODEL NUMBERS - BBRLP48, BBRLP72, BBRLP96

## LOW HEIGHT REMOTE BACK BAR REFRIGERATOR

MODEL NOS.		BBRLP48	BBRLP72	BBRLP96
NUMBER OF DOORS		2	3	4
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	48 (1219)	72 (1829)	96 (2438)
	Depth - in. (mm)	24¾ (629)	24¾ (629)	24¾ (629)
	Height - in. (mm)	29 (736)	29 (736)	29 (736)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	44 (1118)	68 (1727)	92 (2337)
	Depth - in. (mm)	18¾ (476)	18¾ (476)	18¾ (476)
	Height - in. (mm)	25⅞ (646)	25⅞ (646)	25⅞ (646)
INTERNAL VOLUME Net. Cu. Ft. (Litres)		12.6 (357)	19.8 (561)	27.0 (765)
PRODUCT CAPACITY	Case Packed - 12 Oz. Bottle/Can	221/391	351/648	468/882
	Staggered - 12 Oz. Bottle/Can	255/490	398/723	540/993
SHIPPING WEIGHT Lbs. (kg.)		250 (113)	340 (154)	465 (210)
ELECTRICAL SPECIFICATIONS	Electrical Supply	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph
	Running Load Amps	1.6	2	2.5
	Electrical Connection	Hard wired	Hard wired	Hard wired
	Defrost Initiation	Automatic	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle	Off cycle
	Lighting Type	LED	LED	LED
REFRIGERATION SPECIFICATIONS	Evaporator Capacity - Remotes	1900 Btu/Hr @ 20° F Evaporator	2300 Btu/Hr @ 20° F Evaporator	2300 Btu/Hr @ 20° F Evaporator
	Remote Refrigerant Options	R134a and R404a	R134a and R404a	R134a and R404a
PLUMBING	Evaporator Condensate	Field plumbed	Field plumbed	Field plumbed

Wine Temperature refrigerators do not carry NSF Rating for open food storage.

Wine Temperature units are NSF certified for non-potentially hazardous bottled and canned beverage storage.

- Remote units are made to order and non-returnable

### WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at [perlick.com](http://perlick.com). Or to find out more about Prop 65, go to [P65Warnings.ca.gov](http://P65Warnings.ca.gov).

Form No. Z2428  
Rev. 04.14.25



# PERLICK®



MODEL NUMBERS - BBRLP48, BBRLP72, BBRLP96

## LOW HEIGHT REMOTE BACK BAR REFRIGERATOR

Note: Open floor drain not provided on models intended for non-packaged food.

