

FLOW RATES OF 10 GPM OR LESS

CES 9100 SERIES

Twin Tank Water Softener

- 3/4" porting
- Hardness removal up to 35,080 grains per tank
- Flow rates up to eight (8) gallons per minute continuous
- Meter initiated regeneration for CES-9100E-24
- Sensor initiated regeneration for CES-9100TS E-30

Designed for operations with low volume soft water usage and limited space:

- Cold water fed warewashing
- Laundry - linen & uniform
- General housekeeping
- Water heater scale protection/reduction
- Reverse osmosis pretreatment
- Tea brewing



SPECIFICATIONS

MODEL	PART NUMBER	TANK	RATED CAPACITY @15 LBS. SALT/ CU. FT. (GRAINS)	SERVICE FLOW RATE		PIPE SIZE (IN)	RESIN VOLUME (FT ³) PER TANK	SYSTEM DIMENSIONS* W X D X H (INCHES)	BRINE TANK SALT CAPACITY (LBS)	SHIP WT (LBS)
				CONTINUOUS @ 15 PSI DP (GPM)	INTERMITTENT @ 25 PSI DP (GPM)					
CES-9100E-24	DEV998049	Twin	22,987	7.9	N/A	3/4"	0.75	36 x 13 x 48	125	175
CES-9100TS-30	EV998065	Twin	35,080	8	N/A	3/4"	1	36 x 13 x 52	125	155

*When determining system space requirements, refer to spec sheet for physical arrangement. Installations requiring re-arrangement of tanks, or separation of tanks, may need additional clearance.

FLOW RATES OF 10 GPM OR LESS

Cabinet Softeners

WS SERIES

Single Tank Water Softener

- 3/4" porting
- Hardness removal up to 30,000 grains
- Flow rates up to 10 gallons per minute continuous
- Electronic meter initiated regeneration
- Easily adjustable 5-cycle control

Designed for operations with low volume soft water usage and limited space:

- Cold water fed warewashing
- Boiler scale control
- Laundry - linen & uniform
- Water heater scale protection/reduction
- General housekeeping
- Reverse osmosis pretreatment
- Espresso



SPECIFICATIONS

MODEL	PART NUMBER	TANK	RATED CAPACITY @15 LBS. SALT/ CU. FT. (GRAINS)	SERVICE FLOW RATE		PIPE SIZE (IN)	RESIN VOLUME (FT ³) PER TANK	SYSTEM DIMENSIONS* W X D X H (INCHES)	BRINE TANK SALT CAPACITY (LBS)	SHIP WT (LBS)
				CONTINUOUS @ 15 PSI DP (GPM)	INTERMITTENT @ 25 PSI DP (GPM)					
WS-30E (120V/50-60Hz)	EV9980-58	Single	30,000	10	N/A	0.75	1	13 x 23 x 45	225	90
WS-30	EV9980-59	Single	30,000	10	N/A	0.75	1	13 x 23 x 45	225	90

*When determining system space requirements, refer to spec sheet for physical arrangement. Installations requiring re-arrangement of tanks, or separation of tanks, may need additional clearance.