Hot Food Holding Carving Station



Alto-Shaam carving stations keep food fresh, hot and ready to serve at just the right temperature. Maximize visual appeal while maintaining food temperature and quality. Gentle, precise Halo Heat® technology radiates directly from the carving shelf surface, while ambient surface lamps keep food warm without cooking or drying out food.



CS-200/S

Standard Features

- Controlled, uniform holding with Halo Heat technology
- Fixed lamp assembly provides additional heat to the product for greater surface temperature control
- NSF- and USDA-listed removable cutting board with integrated gravy lane
- Recessed heated surface to catch drippings
- Heated base provides low, medium or high heat options
- Designed to fit on top of Cook & Hold Ovens, heated holding cabinets, smoker ovens or suitable for placement on any surface
- Optional clear-glass customer breath guard easily slides in place, meeting NSF breath guard specification

Configurations (select one)

□ CS-200 ☐ CS-200/S

Electrical

□ 120V □ 230V

Accessories (select all that apply)

Cutting board

- □ Full size: 21-5/8" x 21-5/8" x 1/2" (550mm x 550mm x 13mm) [BA-49380]
- □ Half size: 10-3/4" x 21-5/8" x 1/2" (273mm x 550mm x 13mm) [BA-49540]

Carving Holders

- □ Prime rib (HL-2635)
- ☐ Steamship round (4459)



70 lb (32 kg) product maximum












CS-200

Specification











Model

Exterior (H x W x D)

CS-200 33-3/16" x 25-3/4" x 29-5/16" [842mm x 654mm x 744mm] CS-200/S 33-3/16" x 26" x 30-13/16" [842mm x 660mm x 782mm] Net Weight 60 lb [27 kg] Contact factory

DIMENSIONS

Ship Weight*

CS-200 150 lb (68 kg) CS-200/S 170 lb (77 kg) Ship Dimensions (L x W x H)*

35" x 35" x 41" [889mm x 889mm x 1041mm] 35" x 35" x 41" [889mm x 889mm x 1041mm]

*Domestic ground shipping information. Contact factory for export weight and dimensions.



- Appliance must be installed on a stable level surface.
- Appliance must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.
- Warranty does not apply if the carving station is flooded or immersed in water.



CS-200	٧	Ph	Hz	Α	kW	Cord & Plug
120V	120	1	60	6.3	0.75	NEMA 5-15p 15A-125V plug
230V	230	1	50/60	3.26	0.75	Plugs rated 250V CEE 7/7
						CH2-16P
						BS 1363
						AS/NZS 3112

CONTACT US

W164 N9221 Water Street | Menomonee Falls, Wisconsin 53051 | U.S.A. Phone: 262.251.3800 | 800.558.8744 U.S.A./Canada | Fax: 262.251.7067 | alto-shaam.com