

PROJECT:		
ITEM#		QTY:
MODEL#		
AIA#	SIS #	
APPROVED:		

CHEF BASE FREEZER

Model: WTFCS60HC

TWO DRAWERS





OPTIONS & ACCESSORIES

- Left side compressor location (-ALT) (specify at time of unit order)
- · Stainless steel back
- · Stainless steel interior
- · Additional pan supports
- 6" Adjustable legs, 6" seismic legs
- 6" Casters
- Gasket guards
- Flat top overhang (up to 6" overhang on each side)
- Remote option*(refrigerant must be specified at time of order, see note on back on page)

7 YEAR WARRANTY Parts, Labor, and Compressor

CABINET CONSTRUCTION

- Stainless steel front, sides, drawers and grille (galvanized back & bottom)
- · Interior liner is made of corrosion resistant aluminum
- Top has full marine edge to prevent spills from dripping over sides
- · Full electronic control
- · Top weight capacity 1000 lbs
- · One-piece, snap-in magnetic drawer gasket
- 12-Gauge stainless steel drawer slides with Delrin® rollers rated at 275 lbs
- · Lifetime warranty on all drawers and slides
- · Heavy duty, fire-proof, insulated 16 gauge top
- No heat shield required (must adhere to proper clearance per owners manual)
- Accommodates 6" deep full size food service pans (not included)
- Self-closing drawer feature
- · Compressor standard on right side
- · 3" Casters, 2 with brakes standard

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- · Adaptive defrost
- · Non-electric defrost with hot gas condensate evaporation
- Freezer capable of maintaining product temperature of -10°F




BEVERAGE-AIR


Chef Base Freezer Model: WTFCS60HC


PLAN VIEW

ELEVATION VIEW

SIDE VIEW







EXTERNAL DIMENSIONAL DATA		
Width Overall (in)	60"	
Depth Overall (in)	34 3/4"	
Height Overall (in)	24 3/8"	
Number of Drawers	2	
Depth with Drawers Extended (in)	57 3/4"	
Drawer Openings (in)	(2) 40 3/8" x 6 1/2"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft).	9.75	
Internal Width Useable (in)	46"	
Internal Width Useable (in) Internal Depth Overall (in)	46" 22 3/8"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, $improvements, additions\ or\ replacements\ for\ previously\ purchased\ equipment.$ Dimensional tolerances +/- 1/4". Metric dimensions (MM).

Required Clearance: Bottom 3 13/16" & Rear 1"

ELECTRICAL DATA		
Full Load Amps	5.0	
Voltage	115/60/1	
Nema Plug (8' cord)	5-15P	
REFRIGERATION DATA		
Horsepower	1/2	
Capacity (BTU/Hr)	1725	
Heat Rejection (BTU/Hr)	2588	
Charge (lbs/grams/ounces)	0.287 / 130 / 4.59	
SHIPPING DATA		
Gross Weight - Crated	475 lbs.	
Height - Crated (in)	27"	
Width - Crated (in)	65"	
Depth - Crated (in)	38"	

ELECTRICAL CONNECTION



115/60/1

Unit pre-wired at factory NEMA 5-15P and include 8' long cord and plug set.

3779 Champion Blvd., Winston-Salem, NC 27105 | 888-845-9800 | Fax: 336-245-6453 | Beverage-Air.com | Sales@bevair.com

Date Issued 9/25 | Printed in U.S.A.

